

Specification

Slip resistance

Gripsure decking made with Accoya® using two non slip inserts will achieve a minimum PTV value of 85 (pendulum test value – see below).

Gripsure non slip decking has been independently tested using the pendulum test (the operation and calibration of which are described in BS7976:2002 parts 1 and 3) operated to the United Kingdom Slip Resistance Group (UKSRG) guidelines see website for full slip test results.

Aggregate inserts

Gripsure non slip decking uses a 0.5mm - 1.4mm double washed and screened Guyanan Calcined Bauxite – grey colour with a minimum PSV (polished stone value) of 70.

Timber board

Gripsure decking made with Accoya® wood uses sustainably grown pine modified by acetylation. This increases the amount of naturally-occurring acetyl molecules and reduces the amount of hydroxyls. Improving the timber's durability, stability and service life. Accoya wood has exceptional durability and is warranted for 50 years above ground and 25 years in-ground or fresh water.

Gripsure decking made with Accoya® is supplied with FSC® timber – Certificate No TT-COC-003864

Board profile dimensions are ex 150mm width x 32mm depth, giving a finished product profile of approximately 142mm x 22mm. Standard lengths available are 2.4m to 4.8m. A bespoke cutting service is available for any lengths.

Maintenance

Gripsure non slip decking made with Accoya® is a low maintenance product, no further preservative treatment is necessary. The timber will weather over time to a grey finish. The boards can be stained or painted if desired. This will have no affect on the performance of the non slip inserts.

Gripsure decking is pressure washable – it is recommended to remove dirt and mould build up across the surface of the board and inserts every 12 months, using a 150bar water pressure washer with fan nozzle at minimum distance of 150mm. Alkaline cleaning products (pH 9 or above) should not be used on Accoya.

Cross cut components

No additional treatment is required for any cuts, notches or drill holes to Gripsure decking made with Accoya®.

Fixing

Stainless steel decking screws (A2 or A4) must be used for fixing Gripsure decking made from Accoya®. When using bearers impregnated with a pigment, isolate the Accoya® deck boards from the bearers.

Contact us for more information today.

 01726 844616

 info@gripsure.co.uk

www.gripsure.co.uk

Unit 2, Rockhill Business Park, Bugle, Cornwall, PL26 8RA