

# Gripsure Ecodek AT Specification

## Slip resistance

Gripsure Ecodek AT using two non slip inserts will achieve a minimum PTV value of 70 (pendulum test value). Gripsure non slip decking has been independently tested using the pendulum test (the operation and calibration of which are described in BS7976:2002 parts 1 and 3) operated to the United Kingdom Slip Resistance Group (UKSRG).

---

## Aggregate inserts

Gripsure non slip decking uses a 0.5mm - 1.4mm double washed and screened Guyanan Calcined Bauxite – grey colour with a minimum PSV (polished stone value) of 70.

---

## Timber board

Gripsure Ecodek is made from a blend of 55% recycled FSC® certified Beech hardwood fibres and 45% recycled plastic milk bottles HDPE polymer. The board has a solid cross-section for strength and durability and can be fitted like traditional decking.

Gripsure Ecodek is supplied with FSC® timber – Certificate No TT-COC-003864

Board profile dimensions are ex 136mm width x 21mm depth, giving a finished product profile of approximately 136mm x 21mm. Lengths available are 1.5m to 6m (3.6m as standard). A bespoke cutting service is available.

---

## Colour

Gripsure Ecodek AT is available in 5 colour options; Black, Slate Grey, Pebble Grey, Dark Brown and Light Brown.

---

## Maintenance

Gripsure Ecodek is a very low maintenance product, no further maintenance is necessary. Gripsure do not recommend painting or staining Gripsure Ecodek boards.

Gripsure recommended to remove dirt and debris build up across the surface of the board and inserts every 12 months, using composite decking cleaning solution with a mop and bucket. Gripsure do not recommend using a pressure washer on Ecodek decking boards.

---

## Cross cut components

No additional treatment is required for any cuts, notches or drill holes to Gripsure Ecodek.

---

## Fixing

Gripsure Ecodek can be fitted just like regular timber decking boards. Colour matching ecodek® decking screws are recommended for fixing Gripsure Ecodek. There are screws available for timber, composite and steel substructures.

Contact us for more information

 01726 844616  [info@gripsure.co.uk](mailto:info@gripsure.co.uk)  [www.gripsure.co.uk](http://www.gripsure.co.uk)

Unit 2, Rockhill Business Park, Bugle Cornwall PL26 8RA

# Gripsure Ecodek Heritage Specification

## Slip resistance

Gripsure Ecodek Heritage using two non slip inserts will achieve a minimum PTV value of 59 (pendulum test value). Gripsure non slip decking has been independently tested using the pendulum test (the operation and calibration of which are described in BS7976:2002 parts 1 and 3) operated to the United Kingdom Slip Resistance Group (UKSRG).

---

## Aggregate inserts

Gripsure non slip decking uses a 0.5mm - 1.4mm double washed and screened Guyanan Calcined Bauxite – grey colour with a minimum PSV (polished stone value) of 70.

---

## Timber board

Gripsure Ecodek is made from a blend of 55% recycled FSC® certified Beech hardwood fibres and 45% recycled plastic milk bottles HDPE polymer. The board has a solid cross-section for strength and durability and can be fitted like traditional decking.

Gripsure Ecodek is supplied with FSC® timber – Certificate No TT-COC-003864

Board profile dimensions are ex 136mm width x 21mm depth, giving a finished product profile of approximately 136mm x 21mm. Lengths available are 1.5m to 6m (3.6m as standard). A bespoke cutting service is available.

---

## Colour

Gripsure Ecodek Heritage is available in 5 colour options; Highland Basalt, Welsh Slate, Cornish Pebble, Pennine Millstone and Brecon Shale.

---

## Maintenance

Gripsure Ecodek is a very low maintenance product, no further maintenance is necessary. Gripsure do not recommend painting or staining Gripsure Ecodek boards.

Gripsure recommended to remove dirt and debris build up across the surface of the board and inserts every 12 months, using composite decking cleaning solution with a mop and bucket. Gripsure do not recommend using a pressure washer on Ecodek decking boards.

---

## Cross cut components

No additional treatment is required for any cuts, notches or drill holes to Gripsure Ecodek.

---

## Fixing

Gripsure Ecodek can be fitted just like regular timber decking boards. Colour matching ecodek® decking screws are recommended for fixing Gripsure Ecodek. There are screws available for timber, composite and steel substructures.

Contact us for more information

 01726 844616  [info@gripsure.co.uk](mailto:info@gripsure.co.uk)  [www.gripsure.co.uk](http://www.gripsure.co.uk)

Unit 2, Rockhill Business Park, Bugle Cornwall PL26 8RA